

RCNS2



RCNS2

**Pneumatic sealer for
steel strapping**

Reliable Performance

Single reverse notch joint ensures load stability

Application Flexibility

Ideal for a wide range of industries, including lumber, metals and other products

Simplifies Operation

Lightweight, ergonomic design streamlines use for difficult applications

Minimizes Downtime

Durable construction provides long-lasting operation

RCNS2

Pneumatic sealer for steel strapping



The RCNS2 pneumatic sealer, available in two models to accommodate varying strapping gauges, is designed for use with high-tensile strapping. Ideal for general use as well as the most challenging sealing applications, the RCNS2 tool simplifies operation to maximize productivity for heavy-duty steel sealing.

Features and benefits

■ Easy to use

The RCNS2 features a lightweight, ergonomic design with one-handed operation, making it ideal for both stationary and non-stationary industrial applications. Its sealing head can easily be pivoted to seal inside tight spaces.

■ Ensures load stability

Manufactured to withstand the rigors of heavy-duty or high-tensile applications, the RCNS2 produces a single reverse notch seal to maximize load strength throughout the transportation cycle.

■ Streamlines maintenance

Made in the USA, the RCNS2 is constructed with all metal and alloy parts that provide long-lasting, low-maintenance operation. With few wear parts to minimize overall maintenance requirements, the RCNS2 is simple to maintain. Wear parts are easily accessible and can be sourced locally through Signode parts and service.



Technical Specifications

Model	RCNS2-34	RCNS2-114
Part Number	424200	424125
Strap Width	3/4" (19.0mm)	1-1/4" (38.1mm)
Strap Thickness	0.025-0.031" (0.64-0.79mm)	
Seals	34 HOC	114 P, 114 E
Joint Type	Single reverse notch	
Tool Weight	9 lbs (4.1 kg)	
Pneumatic Requirements	90 psi (6.2 bar)	